

-40V, -80A P-CHANNEL POWER MOSFET

GENERAL DESCRIPTION


The SFM4008PT uses advanced trench technology and design to provide excellent $R_{DS(on)}$ with low gate charge. It can be used in a wide variety applications.

Features

- ◆ $V_{DS}=-40V, I_D=-80A$
- ◆ $R_{DS(on)}$
TYP: $6.2m\Omega @ V_{GS}=-10V$
TYP: $8.3m\Omega @ V_{GS}=-4.5V$

Applications

- ◆ PWM Applications
- ◆ Power Management
- ◆ Load Switch



ORDERING INFORMATION

Part No.	Package	Marking	Material	Packing
SFM4008PT	PDFN5*6-8L	SFM4008PT	Pb Free	Reel

ABSOLUTE MAXIMUM RATINGS ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Characteristics		Symbol	Ratings	Unit
Drain-Source Voltage		V_{DS}	-40	V
Gate-Source Voltage		V_{GS}	± 20	V
Drain Current	$T_C = 25^{\circ}\text{C}$	I_D	-80	A
	$T_C = 100^{\circ}\text{C}$		-56	
Drain Current Pulsed(Note 1)		I_{DM}	-320	A
Power Dissipation($T_C=25^{\circ}\text{C}$) -Derate above 25°C		P_D	90	W
			0.72	W/ $^{\circ}\text{C}$
Single Pulsed Avalanche Energy (Note 2)		E_{AS}	182	mJ
Operation Junction Temperature Range		T_J	$-55\sim+150$	$^{\circ}\text{C}$
Storage Temperature Range		T_{stg}	$-55\sim+150$	$^{\circ}\text{C}$
Maximum lead temperature for soldering purposes, 1/8" from case for 5 seconds		TL	300	$^{\circ}\text{C}$

THERMAL CHARACTERISTICS

Characteristics	Symbol	MAX	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	1.4	$^{\circ}\text{C}/\text{W}$
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	60	$^{\circ}\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
Drain -Source Breakdown Voltage	B _{VDSS}	V _{GS} =0V, I _D =-250μA	-40	--	--	V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =-40V, V _{GS} =0V	--	--	1.0	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =20V, V _{DS} =0V	--	--	100	nA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =-20V, V _{DS} =0V	--	--	-100	
On Characteristics						
Gate Threshold Voltage	V _{GS(th)}	V _{GS} = V _{DS} , I _D =-250μA	-1.0	-1.6	-2.5	V
Static Drain- Source On State Resistance	R _{DS(on)}	V _{GS} =-10V, I _D =-30A	--	6.2	7.5	mΩ
		V _{GS} =-4.5V, I _D =-20A	--	8.3	10	
Dynamic Characteristics						
Gate Resistance	R _g	V _{GS} =0V; f=1.0MHZ	1	4.0	10	Ω
Input Capacitance	C _{iss}	V _{DS} =-20V V _{GS} =0V f=1.0MHZ	--	6554	--	pF
Output Capacitance	C _{oss}		--	553	--	
Reverse Transfer Capacitance	C _{rss}		--	375	--	
Switching Characteristics						
Turn-on Delay Time	t _{d(on)}	V _{DD} =-20V, I _D =-20A V _{GS} =-10V, R _G =3Ω	--	15	--	ns
Turn-on Rise Time	t _r		--	88	--	
Turn-off Delay Time	t _{d(off)}		--	122	--	
Turn-off Fall Time	t _f		--	101	--	

Total Gate Charge	Q_g	$V_{DS}=-20V, I_D=-20A$ $V_{GS}=-10V$	--	115	--	nc
Gate-Source Charge	Q_{gs}		--	23	--	
Gate-Drain Charge	Q_{gd}		--	20	--	

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

Characteristics	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Continuous Source Current	I_S	Integral Reverse P-N Junction Diode in the MOSFET	--	--	-80	A
Pulsed Source Current	I_{SM}		--	--	-320	
Diode Forward Voltage	V_{SD}	$I_S=-20A, V_{GS}=0V$	--	--	-1.2	V
Reverse Recovery Time	T_{rr}	$V_{GS}=0V, I_S=-20A,$ $dI_F/dt=100A/\mu S$	--	25	--	ns
Reverse Recovery Charge	Q_{rr}		--	17	--	nC

1. Pulse width limited by maximum junction temperature
2. $L=0.5mH, V_{DD}=-20V, V_G=-10V, R_G=25\Omega$, starting $T_J=25^\circ C$
3. Pulse Test: Pulse width $\leq 300\mu s$, Duty cycles $\leq 2\%$
4. Essentially independent of operating temperature

Typical Performance Characteristics

Figure1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5 : Capacitance Characteristics





Figure 6 : Gate Charge Characteristics



Typical Performance Characteristics

Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area







Figure 10: Maximum Continuous Drain Current vs. Case Temperature




Test Circuit



Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveform



Unclamped Inductive Switching Test Circuit & Waveform

Package Dimensions of PDFN5*6-8L



COMMON DIMENSIONS
(UNITS OF MEASURE=MILLIMETER)

SYMBOL	MIN	NOM	MAX
A	1.0	1.1	1.2
b	0.35	0.4	0.45
b1		(0.3)	
c	0.2	0.25	0.35
D	5.9	6.05	6.2
D1	5.65	5.75	5.85
D2		(3.475)	
E			5.2
E1	4.9	5	5.1
E2		(4.01)	
e		1.27BSC	
H	0.5	0.65	0.75
L	0.51	0.635	0.75
L1		0.15	
θ		10°	

Disclaimer:

- ▶ Hi-semicon reserves the right to make changes to the information herein for the improvement of the design and performance without further notice! Customers should obtain the latest relevant information before placing orders and should verify that such information is complete and current.
- ▶ All semiconductor products malfunction or fail with some probability under special conditions. When using Hi-semicon products in system design or complete machine manufacturing, it is the responsibility of the buyer to comply with the safety standards strictly and take essential measures to avoid situations in which a malfunction or failure of such Hi-semicon products could cause loss of body injury or damage to property.
- ▶ Hi-semicon will supply the best possible product for customers!